



△				
---	--	--	--	--

SPECIFICATION		
HOISTING LOAD	0.25 TON	
TESTING LOAD	0.313 TON	
LIFTING HEIGHT	Min. 3.5 M ~ Max 40 M	
HOISTING	SPEED	8.4 M/MIN
	MOTOR	0.5 Kw x 4 POLE
POWER SUPPLY	3Φ-220,380,440,460,480V-60Hz	
CONTROLL VOLTAGE	1Φ -48,110V -60Hz	
OPERATING METHOD	PUSH BUTTON TYPE	
LOAD CHAIN SPEC.	Φ5.0 x 15P x 1 FALLS	
RATING	30 MIN	
NET WEIGHT	Min. 25 KG	

NO.	DESCRIPTION	MAT'L	SIZE	Q'TY	REMARK
710	OVER LIMITER			1	
700	ELEC. ASS'Y			1	
600	HOIST MOTOR ASS'Y			1	
500	BUCKET ASS'Y			1	
400	BOTTOM HOOK ASS'Y			1	
300	TOP HOOK ASS'Y			1	
200	GEAR BOX ASS'Y			1	
100	CENTER FRAME ASS'Y			1	



TITLE OF PROJECT 0.25TON SUSPENSION TYPE
ELEC. CHAIN HOIST GENERAL ASSEMBLY

DRAWN	CHECKED	SCALE	DWG. NO.
DESIGNED	APPROVED	DATE	
	전 승 현	2008.1.15	SCO-S250