



△				
---	--	--	--	--

SPECIFICATION	
HOISTING LOAD	2 TON
TESTING LOAD	2.5 TON
LIFTING HEIGHT	Min. 3 M ~ Max 40 M
HOISTING	SPEED 3.5/1.75 M/MIN
	MOTOR 1.5/0.75 Kw x 4 P
POWER SUPPLY	3Φ-220,380,440,460,480V-60Hz
CONTROLL VOLTAGE	1Φ -48,110V -60Hz
OPERATING METHOD	PUSH BUTTON TYPE
LOAD CHAIN SPEC.	Φ7.1 x 21P x 2 FALL
RATING	30 MIN.
NET WEIGHT	APPROX Min. 70KG~Max. 105KC

DIMENSIONS					
구분 기호	양정(LIFT)				
	3M~11M	12M~16M	17M~20M	21M~30M	31M~40M
P	250	265	280	280	300
C	630	825	990	1100	1350

MODEL : SMO-D2000

800	AUX. ELECT. ASS'Y				1	
700	ELEC. ASS'Y				1	
600	HOIST MOTOR ASS'Y				1	
500	BUCKET ASS'Y				1	
400	BOTTOM HOOK ASS'Y				1	
300	TOP HOOK ASS'Y				1	
200	GEAR BOX ASS'Y				1	
100	CENTER FRAME ASS'Y				1	
NO.	DESCRIPTION	MAT'L	SIZE	Q'TY	REMARK	

	TITLE OF PROJECT 2 TON SUSPENSION DUAL TYPE (LIFT : 3M~40M)			SCALE 1/1	
	ELEC. CHAIN HOIST GENERAL ASSEMBLY			DATE 2005.7.20	
DRAWN S.M.YOO	CHECKED S.S.CH	DESIGNED S.S.CH	APPROVED S.S.CH	MM INCH	