SPECtite

PRIMER PU HP 1000

One component, polyurethane based primer material. Contains solvent.

Mainly used before polyurethane based materials's applications. AS 014 used for increasing corrosion resistance of mineral based surfaces. Give high adhere power before the application of polyurethane coatings.

Product advantages:

- Easy application
- Low cost
- Perfect adhesion to minerals and concrete surfaces.
- Solvent
- Transparent
- High resistance to all weather conditions (-30ºC /+120ºC)
- Decraese the water absorb of the concrete.
- Get harden of the concrete surface
- Support two grade protection
- Water resistance

Application:

- There is no need to any other components. It is ready to use in its package.
- Apply with roller or brush.
- Surface should protect from water, rain for 3-4 hours

Technical specifications:

- Component : one (ready to use)
- Base : Polyurethane
- Application temperature : Above +5ºC
-

- Consumption : 100 grm-200 grm/m²
- Dry : 3-8 hours
- Package : 4 kg galon, 15 kg drum

Surface:
Careful surface preparation is essential for optimum finish and durability so application surface need to be dry,clean and hard. It should be cleaned out from dirt,oil,paint,dust. According to absorbent of the surface,application should done 2 layer. Dry time between layers is; 2-3 hours.

Storage:
Pails should be stored in a dry and cool rooms for up to 9 months. Protect the material against moisture and direct sunlight.Production date is on label. Packages should be stored upward.

Caution:
Do not apply in closed areas because of solvent scent .It is flammable so do not come closer with a flame. Do not smoke while application. Application should be done at open areas or air contioned places.Use eye shild,glove and protecter clothes.If it touches with skin wash with water and soap. Do not use the empty packages for the storage of nutriment.

The information and recommendations contained herein are based on the current state of our knowledge. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained here.

Whilst the information and/or specifications given are, to the best of our knowledge, true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents or distributors as the conditions of use and labour involved are beyond our control.

If it is proven that the product does not perform as described in our TDS, SpEC's liability extends solely to the free replacement of product, once the claim has been accepted after due investigation by SpEC. SpEC will not entertain any claims involving any form of consequential costs or damages such as shipping costs, custom duties, damages to third parties, damages to structures, penalties from delay of a project or any other form of consequential damage.

SPECIALITY ENGINEERING CHEMICALS
PO Box 61347, Dubai, United Arab Emirates. Telephone: +971 4 883 6662, Fax: +971 4 883 7696
E-mail: info@spec.ae; Skype ID: spec.sales
www.spec.ws